ورقة المواصفات المترجمة

الصفحة الأصلية 1

كشاف يدوي LED مقاوم للانفجار مع وصلة تمديد
DWXP
معلومات المنتج
المنتج المناسب، بتصنيع متقن، في الموعد، في كل مرة
هالتوم سيتي، TX | باتون روج، www.worksitelighting.com | 877) 861-5255) 440.4141 (817) | LA
كشاف يدوي مقاوم للانفجار مع وصلة تمديد من Worksite Lighting:
حل متعدد الاستخدامات وعالي الأداء للبيئات ذات المتطلبات الصعبة
يوفر الكشاف اليدوي المقاوم للانفجار من Worksite Lighting
إضاءة موثوقة وعالية الشدة للبيئات الخطرة التي يحتمل أن تكون
قابلة للانفجار. متوفر بكلا
الإصدارين بجهد 120 فولت و12 فولت، ومجهز بـ
قابس مقاوم للانفجار، وقد صمم هذا الكشاف اليدوي بخبرة
لتحقيق السلامة والأداء معا.
مقاومة للانفجار:
يحمي من تأثير الأبخرة لتوفير إضاءة آمنة،
إضاءة فعالة في بيئات المواقع الخطرة التي
قد توجد فيها غازات قابلة للاشتعال.
متوافق مع متطلبات OSHA:
يفي صراحة بمعايير OSHA الخاصة بإضاءة الأماكن المحصورة
إضاءة لتعزيز السلامة في مكان العمل.
آمنة
توفر الإضاءة المقاومة للانفجار مستوى عاليا من السلامة
مزايا في البيئات الخطرة، من خلال منع
حالات الاشتعال الناتجة عن الأبخرة أو الغازات القابلة للاشتعال. وبفضل كونها
محكمة الإغلاق ضد الرطوبة والجسيمات العالقة في الهواء، فإن هذه المصابيح
تضمن أداء موثوقا مع الحد من المخاطر. هذا
التصميم الذي يركز على السلامة يعزز أمان
أماكن العمل التي تواجه باستمرار ظروفا
صعبة.

الصفحة الأصلية 2

المنتج المناسب، بتصنيع متقن، في الموعد، في كل مرة
هالتوم سيتي، TX | باتون روج، www.worksitelighting.com | 877) 861-5255) 440.4141 (817) | LA
امسح لزيارة موقعنا الإلكتروني

يقدم فريقنا خدمات صيانة وإصلاح سريعة وشاملة لجميع منتجاتنا، مما يضمن استمرارية الأداء و طول العمر التشغيلي. نوفر الدعم في الموقع وعن بعد، بما يلبي احتياجاتكم الخاصة. اعتمدوا علينا لتوفير صيانة استباقية وحل سريع للمشكلات للحفاظ على الكفاءة التشغيلية.

تصنيفات وحدات الإنارة المقاومة للانفجار

أمريكا الشمالية

Class I، القسم ا، المجموعتان C وD

Class II، القسم ا، المجموعتان F وG

Class I, Zone I, Group IIB

فئة درجة الحرارة: T4

كندا

Class I، القسم ا، المجموعتان C وD

Class II، القسم ا، المجموعتان F وG

Class I, Zone I, Group IIB

فئة درجة الحرارة: T4

المواصفات

الصيانة والإصلاح:

المواصفات:

الوزن: 10 lbs. (وحدة الإنارة وسلك التوصيل)

الجهد: 12 = DW EXPLOSION PROOF أو 120V

نوع المصباح: 1500 ,10W LED لومن, 5000K CCT

الكابلات: كابل بطول 50’,100‘ قياسي، اختياري حتى 250’

القوابس: NEMA 5-15P قابس XP,

كشاف يدوي LED مقاوم للانفجار مع وصلة تمديد DWXP

المستند الأصلي

EXPLOSION PROOF LED HANDLAMP EXTENSION

DWXP

Made in USA

PRODUCT INFORMATION

Worksite Lighting Explosion Proof Extension Handlamp: A Versatile, High-Performance Solution for Demanding Environments

The Worksite Lighting Explosion Proof Handlamp delivers reliable, high-intensity illumination for hazardous, potentially explosive environments. Available in both 120-volt and 12-volt variants and equipped with an explosion-proof plug, this handlamp is expertly designed for both safety and performance.



EXPLOSION PROOF:

Safeguards against vapor interference to deliver safe, effective lighting in hazardous location environments where ignitable gases may be found.

OSHA COMPLIANT:

Explicitly fulfills the OSHA standards for confined space lighting for increased workplace safety.

SAFE

Explosion proof lighting offers substantial safety advantages in hazardous environments, preventing ignitions caused by flammable vapors or gases. By being sealed against moisture and airborne particles, these lights ensure reliable performance while mitigating risks. This safety-focused design enhances the security of workspaces that frequently encounter challenging conditions.

EXPLOSION PROOF LED HANDLAMP EXTENSION

DWXP

SPECIFICATIONS

Service and Repair:

Our team provides prompt, thorough service and repair for all our products, ensuring extended performance and longevity. We offer both on-site and remote support, tailored to your individual needs. Trust us for proactive maintenance and swift issue resolution to uphold operational efficiency.

RATINGS FOR EXPLOSION PROOF LIGHT FIXTURES

NORTH AMERICA

Class I, Division I, Groups C and D
Class II, Division I, Groups F and G
Class I, Zone I, Group IIB
Temperature Rating: T4

CANADA

Class I, Division I, Groups C and D
Class II, Division I, Groups F and G
Class I, Zone I, Group IIB
Temperature Rating: T4

Specifications:

Weight:	10 lbs. (fixture & cord)
Voltage:	DW EXPLOSION PROOF = 12 or 120V
Lamp Type:	10W LED, 1500 lumens, 5000K CCT
Cords:	50',100' cord standard, optional to 250'
Plugs:	NEMA 5-15P XP PLUG,

Scan to visit our website