Mactronic®

TRUSTED BY PROS®

MAVERICK

ANSI FL1 STANDARD | **595 lm** | **170 m**

AHL0053

APPLICATIONS: EDC, OUTDOOR, HIKING, TREKKING, WORK SAFETY, INDUSTRY, ENERGY

POWER SUPPLY	Li-Po 3,7V 800 mAh / 3 x AAA			
CHARGING TIME	2 h 30 min			
	LIGHT OUTPUT	**RUN TIME**	**BEAM DISTANCE**	**PEAK BEAM INTENSITY**
HIGH (Li-Po)	530 lm	2 h 30 min	170 m	7236 cd
MEDIUM (Li-Po)	240 lm	5 h 50 min	115 m	3386 cd
LOW (Li-Po)	30 lm	22 h 30 min	40 m	400 cd
FLASHING 2 Hz (Li-Po)	-	1 h 30 min	-	-
HIGH (3 x AAA)	595 lm	2 h 30 min	170 m	7295 cd
MEDIUM (3 x AAA)	275 lm	6 h	110 m	3145 cd
LOW (3 x AAA)	35 lm	35 h	40 m	415 cd
FLASHING 2 Hz (3 x AAA)	-	1 h 30 min	-	-
DIMENSIONS	62 x 45 x 46 mm			
WEIGHT	88 g (without battery), 109 g (with battery)			
THE SET INCLUDES	Li-Po battery, USB-C cord, headband			



ADDITIONAL ACCESORIES:

AHL0053B	Li-Po 3,7V 800 mAh rechargeable battery (USB-C)
AHL0051M	Helmet mount with double-sided hook and loop







IP64 RATING | **2 m IMPACT RESISTANCE** | **USB-C CHARGING** | **DUAL SOURCE SYSTEM**

FOCUS | **MOTION SENSOR** | **ADVANCED DIMMING SYSTEM**

Maverick headlamp delivers 595 lumens of light and offers four modes, allowing you to adjust brightness for various needs. It features an adjustable focus and a motion sensor for automatic activation. The beam distance reaches up to 170 meters, with 2 hours and 30 minutes running in High mode. The headlamp can be powered by a USB-C rechargeable battery or three AAA batteries. An IP64 rating protects it against dust and water splashes, and its 2-meter impact resistance to drops enhances durability. This versatile tool is ideal for outdoor activities, DIY projects, and everyday use.

PRODUCT MEETS THE FOLLOWING STANDARDS: CE RoHS

MACTRONIC® VALUE HIGHLIGHTS

5-YEAR WARRANTY | **PATENTED DESIGN** | **ECO FRIENDLY PACKAGING**

SCAN ME

Mactronic® Group Sp. z o. o., ul. Stargardzka 4, 54-156 Wrocław, Poland | +48 71 351 86 53 | export@mactronic.pl | www.mactronic.pl/en