Mactronic®

TRUSTED BY PROS®

MAVERICK

ANSI FL1 STANDARD | **750 lm** | **174 m**

AHL0054

APPLICATIONS: EDC, OUTDOOR, HIKING, TREKKING, WORK SAFETY

POWER SUPPLY	Li-Po 3,6V 1000 mAh / 3 x AAA			
CHARGING TIME	1 h 30 min			
	LIGHT OUTPUT	**RUN TIME**	**BEAM DISTANCE**	**PEAK BEAM INTENSITY**
HIGH (Li-Po)	750 lm	3 h 30 min	174 m	7568 cd
MEDIUM (Li-Po)	310lm	6 h 50 min	110 m	3006 cd
LOW (Li-Po)	40 lm	28 h	40 m	405 cd
FLASHING* (Li-Po)	-	1 h 40 min	-	-
HIGH (3 x AAA)	600 lm	2 h 30 min	170 m	6900 cd
MEDIUM (3 x AAA)	250 lm	6 h	110 m	2806 cd
LOW (3 x AAA)	40 lm	35 h	40 m	493 cd
FLASHING* (3 x AAA)	-	2 h 30 min	-	-
DIMENSIONS	62 x 45 x 46 mm			
WEIGHT	49,7 g (without battery), 71,1 g (with Li-Po battery)			
THE SET INCLUDES	Li-Po battery, USB-C cord, headband			

*Outside ANSI FL1 Scope









IP64 RATING

2 m IMPACT RESISTANCE

USB-C CHARGING

DUAL SOURCE SYSTEM

FOCUS

MOTION SENSOR

ADVANCED DIMMING SYSTEM

Maverick headlamp delivers 750 lumens of light and offers four modes, allowing you to adjust brightness for various needs. It features an adjustable focus and a motion sensor for automatic activation. The light beam reaches up to 174 meters, with 3 hours and 30 minutes running in High mode. The headlamp can be powered by a USB-C rechargeable battery or three AAA batteries. An IP64 rating protects it against dust and water splashes, and its 2-meter impact resistance to drops enhances durability. This versatile tool is ideal for outdoor activities, DIY projects, and everyday use.

PRODUCT MEETS THE FOLLOWING STANDARDS: CE RoHS

MACTRONIC®
VALUE HIGHLIGHTS

5-YEAR WARRANTY

PATENTED DESIGN

ECO FRIENDLY PACKAGING

SCAN ME

Mactronic® Group Sp. z o. o., ul. Stargardzka 4, 54-156 Wrocław, Poland | +48 71 351 86 53 | export@mactronic.pl | www.mactronic.pl/en