EXPLOSION PROOF LED HANDLAMP

WORKSITE LIGHTING AND POWER SOLUTIONS

TRICERT LED HANDLAMP



Key Features:

- Triple-certified: ATEX, IECEx, and UL / CSA.
- 15 W / 2,460 lm or 25 W / 4,100 lm.
- 12-24 V or 120-277 V options.
- Copper-free aluminum housing; IP66; IK08.

Technical Specifications

Specifications	TriCert Handlamp
Model options	WL-THL-15-LV: 12-24 V, 15 W / 2,460 lm WL-THL-25-LV: 12-24 V, 25 W / 4,100 lm WL-THL-15-HV: 120-277 V, 15 W / 2,460 lm WL-THL-25-HV: 120-277 V, 25 W / 4,100 lm
ATEX	SGS25ATEX0007X II 2G Ex db mb IIC T6/T5 Gb; II 2D Ex tb IIIC T80/95°C Db
IECEx	IECEx SGS 25.0004X Ex db eb mb IIC T6/T5 Gb; Ex mb tb IIIC T80/95°C Db
UL / CSA	Class I Div. 1 Groups C, D; Class I Div. 2 Groups A-D; Class II Div. 1 Groups E-G; Class II Div. 2 Groups F, G; Class III
Housing	Copper-free die-cast aluminum; durable epoxy coating
Protection	IP66 ingress protection; IK08 impact resistance
Weight	Approx. 2.3 kg (5 lb)
Cord options	25, 50, 75, 100, 150, or 200 ft