

XP Proof Inline Handlamp

DWVP-XP



PRODUCT INFORMATION

Worksite Explosion Proof In-line Handlamp: A Versatile, High-Performance Solution for Demanding Environments

The Worksite Lighting Explosion Proof Inline Handlamp is a cautiously crafted lighting solution for strenuous applications demanding vapor-proof utilities. This handlamp ensures dependable, sustained, OSHA-compliant illumination for confined spaces, available in both 24-volt and 12-volt versions. It promises reliable performance across diverse challenging operational environments.

EXPLOSION PROOF:

Safeguards against hazardous vapor interference to deliver safe, effective lighting in wet and damp environments where it is typically found.

OSHA COMPLIANT:

Explicitly fulfills the OSHA standards for confined space lighting in wet and damp locations for increased worker safety.

SAFE

Explosion proof lighting offers substantial safety advantages in hazardous environments, preventing ignitions caused by flammable vapors or gases. By being sealed against moisture and airborne particles, these lights ensure reliable performance while mitigating risks. This safety-focused design enhances the security of workspaces that frequently encounter challenging conditions.



XP Proof Inline Handlamp

DWVP-XP



SPECIFICATIONS

Service and Repair:

Our team provides prompt, thorough service and repair for all our products, ensuring extended performance and longevity. We offer both on-site and remote support, tailored to your individual needs. Trust us for proactive maintenance and swift issue resolution to uphold operational efficiency.

RATINGS FOR VAPOR PROOF LIGHT FIXTURES

NORTH AMERICA

Class I, Division I, Groups C and D
Class II, Division I, Groups F and G
Group IIB Temperature Rating: T4
Nema 4X Wet Location

CANADA

Class I, Division I, Groups C and D
Class II, Division I, Groups F and G
Group IIB Temperature Rating: T4
Nema 4X Wet Location

Specifications:

- Weight:** 10 lbs. (fixture & cord)
- Voltage:** DW XP Proof = 12 or 24 V
INLINE TRANSFORMER 240-24V 120-24V 02. T +/- 0T
- Lamp Type:** / . U LED, /3. . lumens, 5000K
- Cords:** CCT 3. ' cord standard, optional to
- Plugs:** 250T' 15A, 125Vac, NEMA 5-15



Scan to visit our website