

XP Proof Inline Handlamp

DWXP-LED-IL



PRODUCT INFORMATION

Worksite Explosion Proof In-line Handlamp: A Versatile, High-Performance Solution for Demanding Environments

Worksite Lighting's Explosion Proof Hand Lamp with an in-line step-down transformer is a rugged, OSHA-compliant industrial lighting solution tailored for hazardous location environments, featuring Class 1 Division 1 explosion-proof and watertight construction to prevent vapor ignition and ensure reliable illumination in hazardous, wet, or confined areas, while its configurable transformer efficiently converts 240V or 120V input to 12V or 24V output (with custom voltage options available) to meet your site-specific requirements and deliver continuous, code-compliant performance across demanding operational settings.

EXPLOSION PROOF:

A Class 1 Division 1 portable hand-lamp features an explosion-proof, watertight construction that safeguards against hazardous vapor ignition, ensuring safe and reliable illumination even in wet or damp environments commonly found in refineries, chemical plants, and other high-risk areas.

OSHA COMPLIANT:

Explicitly fulfills the OSHA standards for confined space lighting in wet and damp locations for increased worker safety.



Service and Repair:

Our team provides prompt, thorough service and repair for all our products, ensuring extended performance and longevity. We offer both on-site and remote support, tailored to your individual needs. Trust us for proactive maintenance and swift issue resolution to uphold operational efficiency.

RATINGS FOR VAPOR PROOF LIGHT FIXTURES

NORTH AMERICA

Class I, Division I, Groups C and D
Class II, Division I, Groups F and G
Group IIB Temperature Rating: T4
Nema 4X Wet Location

CANADA

Class I, Division I, Groups C and D
Class II, Division I, Groups F and G
Group IIB Temperature Rating: T4
Nema 4X Wet Location

Specifications:

Weight: 10 lbs. (fixture & cord)
Voltage: DW XP Proof = 12 or 24 V
INLINE TRANSFORMER 240-24V 120-24V 240V - 12V
Lamp Type: 10W LED, 1500 lumens, 5000K
Cords: CCT 50' cord standard, optional to
Plugs: 250V' 15A, 125Vac, NEMA 5-15



Scan to visit our website