



Electrical Information								
Model No.	HA06-020	HA06-030	HA06-040	HA06-050	HA06-060	HA06-070	HA06-080	HA06-100
Power Consumption(±5%)	20W	30W	40W	50W	60W	70W	80W	100W
Power Supply	SOSEN((No option for 20W)) / INVENTRONICS/ MOONS((No option for 20W))							
Input Voltage	100-277Vac/277-480Vac((No option for 20W)), 50 / 60 Hz							
Emergency model	EM Wattage & EM time		9W 1.5h (Input Voltage: 100-277Vac, 50 / 60 Hz)					
	Battery Capacity		6.4V 3200mAh					
Power Factor	>0.90							
Surge Protection	4kV line-line, 6kV line-earth				6kV line-line, 10kV line-earth			
Driver Type	Constant Current (CC)							
Control	1-10V							

Description

HA06 is a certified LED Luminaire for Hazardous Locations with waterproof, dustproof, anti-corrosion and shock resistance, well combination of robust structure and outstanding appearance. It's an ideal solution for all types of harsh and hazardous applications.

Key Features

- Seven wattages 20W, 30W, 40W, 50W, 60W, 70W, 80W, 100W, efficiency up to 160lm/w, lumen packages from 3200lm to 16000lm.
- Warm white-cool white color(2000K-6500K) and colored LED R/G/B/AMBER optional.
- Various installation methods such as ceiling mount, trunnion mount, hoop mount, loop mount and pendant mount, are available to meet different installation demands.
- Emergency lighting 9W 1.5 hours
- Well sealed with special structure and materials.
- IP66 & IK08 double protection.

Applications

- Chemical
- Oil, gas and petrochemical
- Pulp and paper
- Foundries
- Manufacturing
- Waste and sewage treatment
- Power generation
- Paint spray booths and so on

Lifespan and Warranty

Operating Temperature	See Table 1 for non-emergency model See Table 2 for emergency model
	77000hrs-L90
Life Time of LED @Ta=25°C	175200hrs-L80 282900hrs-L70
Warranty	5 Years

Temperature class and Working temperature

Rated Power	Tamb	T-Code	
		CL I	CL II & CL III
20W/30W/40W	-40°C to +55°C	T5	T5
50W	-40°C to +45°C	T5	T5
60W/70W/80W	-40°C to +55°C	T5	T5
100W	-40°C to +40°C	T5	T5

Table1 (Non-emergency)

Rated Power	Tamb	T-Code	
		CL I	CL II & CL III
20W/30W/40W	0°C to +55°C	T5	T5
50W	0°C to +45°C	T5	T5
60W/70W/80W	0°C to +55°C	T5	T5
100W	0°C to +40°C	T5	T5

Table2 (Emergency)

Optic Information

LED Type	LED 3030							
Luminous Flux (±10%)	3200 lm	4800 lm	6400 lm	8000 lm	9600 lm	11200lm	12800 lm	16000 lm
Efficacy(5000K Ra70)	160lm/W							
Correlated Color Temperature	5000K (2000K,2200K,2500K,2700K,3000K,3500K,4000K, 4500K,5700K,6500K optional)/Red,Green,Blue,Amber							
Color Rendering Index	Ra70/Ra80/Ra90							
Beam Angle	T00C05/ T00C06/ F01601/ F01602/ F01603/ F01604/ F01605 / F01606/ F01608/ F01609/ F01610/ F01611/ F01612/ F01613							
UGR level	/							

Dimensions and Mount

Product Dimension mm (inch)	Ceiling Mount		618x150x202 (24.33"x5.91"x7.96")	1232x150x202 (48.50"x5.91"x7.96")
	Luminaire Net Weight	Trunnion Mount		618x120x202 (24.33"x4.73"x7.96")
Pendant Mount		618x120x178 (24.33"x4.73"x6.99")	1232x120x178 (48.50"x4.73"x6.99")	
Loop Mount		618x125x218 (24.33"x4.91"x8.57")	1232x125x218 (48.50"x4.91"x8.57")	
Hoop Mount		618x125x225 (24.33"x4.91"x8.84")	1232x125x225 (48.50"x4.91"x8.84")	
Recessed Mount		618x170x114 (24.33"x6.69"x4.85")	1232x170x114 (48.50"x6.69"x4.85")	
Gross Weight	Ceiling Mount		3.4kg (7.48Lbs)	5.0kg (11Lbs)
	Trunnion Mount		3.5kg (7.7Lbs)	5.1kg (11.22Lbs)
	Pendant Mount		3.3kg (7.26Lbs)	4.9kg(10.78Lbs)
	Loop Mount		3.4kg (7.48Lbs)	5.0kg (11Lbs)
	Hoop Mount		3.5kg (7.7Lbs)	5.1kg (11.22Lbs)
Export Carton Size mm (inch)	Recessed Mount		3.4kg (7.48Lbs)	5.0kg (11Lbs)
	Ceiling Mount		4.0kg (8.8Lbs)	5.9kg (12.98Lbs)
	Trunnion Mount		4.1kg (9.02Lbs)	6.0kg (13.2Lbs)
	Pendant Mount		3.9kg (8.58Lbs)	5.8kg(12.76Lbs)
	Loop Mount		4.0kg (8.8Lbs)	5.9kg (12.98Lbs)
Mounting Option	Hoop Mount		4.1kg (9.02Lbs)	6.0kg (13.2Lbs)
	Recessed Mount		4.0kg (8.8Lbs)	5.9kg (12.98Lbs)
	Ceiling mount / Trunnion mount / Pendant mount / Loop Mount / Hoop Mount / Recessed Mount			

Cable Entry	Pendant Mount: 3/4"NPT, 1"NPT, M25*1.5, M32X1.5 Ceiling Mount / Trunnion Mount/Hoop Mount/Loop Mount/Recessed Mount: M25X1.5, M20X1.5, 3/4"NPT, 1/2"NPT
-------------	--

Material	Body: Fiberglass reinforced polycarbonate Lens(outside): Clear Polycarbonate / Diffused Polycarbonate
Finish	Surface non-spraying
Fixture Color	Grey
EPA	0.09m ² (0.96ft ²) 0.18m ² (1.91ft ²)
IK Rating	IK08
IP Rating	IP66


* The tolerance for weight is ±6%.

Certifications and Compliances


Class I, Division 2, Groups A, B, C, D
Class II, Division 2, Groups F, G
Class III
Simultaneous Presence

Suitable for Use Wet Locations
Suitable for Marine locations
Emergency Battery Back-up
IP66


Model description




Photometry




T00C05 (No lens / CP)




T00C06 (No lens / DP)




F01601




F01602




F01603




F01604




F01605




F01606




F01608




F01609




F01610



F01611




F01612



F01613

Mounting Options




Ceiling Mount




Trunnion Mount




Pendant mount



Loop Mount



Hoop Mount




Recessed Mount

Dimensions



Cable entry from the top

Cable entry from the side


Unit: mm (inch)




Loop Mount




Pendant Mount



Hoop Mount



Recessed Mount




Notice: 2ft include: 20W, 30W, 40W, 50W 4ft include: 60W, 70W, 80W, 100W




Ceiling Mount
 Dimension: 150*30*100mm
 Surface Treatment: Powder coating
 Color: Grey

Code: BC-HA06-01




Trunnion Mount
 Dimension: 86*43*100mm
 Surface Treatment: Powder coating
 Color: Grey

Code: BC-HA06-02



Hoop Mount
 Dimension: 119*25*122mm
 Surface Treatment: Powder coating
 Color: Grey

Code: BC-HA06-03




Loop Mount
 Dimension: 119*25*115mm
 Surface Treatment: Powder coating
 Color: Grey

Code: BC-HA06-04




Pendant Mount
 Dimension: $\Phi 33 \times 65$ mm
 Surface Treatment: Surface passivation
 Color: Stainless steel color
 Tube specification: M25X1.5 or 3/4"NPT
 Cable outer diameter: 8-12

Code: BC-HA06-05



Pendant Mount
 Dimension: $\Phi 41 \times 65$ mm
 Surface Treatment: Surface passivation
 Color: Stainless steel color
 Tube specification: M32X1.5 or 1"NPT
 Cable outer diameter: 15-19

Code: BC-HA06-06



Recessed Mount
 Dimension: 170*30*90mm
 Surface Treatment: Powder coating
 Color: Grey

Code: BC-HA06-07