

RoughReady

WORKSITE
LIGHTING AND POWER SOLUTIONS

The Rough Ready magnet light provides portable, explosion-proof LED lighting, engineered to thrive in hazardous and industrial environments where safety and reliability are paramount.

CLASS I DIV. 1

CLASS II DIV. 1

CLASS I DIV. 2

CLASS III

UL 1598

UL 1598A

Key Features

1. Lightweight & Compact

Low profile and lightweight design is perfect for portable use in confined spaces for applications like sandblasting and tank cleaning.

2. High Efficiency

Delivers up to 160 lm/W, utilizes special-treated glass for extreme application, providing high efficacy and long life.

3. Magnetic Mount

The magnetic mount offers unmatched convenience, allowing the light to securely attach to metallic surfaces for hands-free operation in challenging environments. This feature ensures quick and easy placement, even in tight or hard-to-reach areas, enhancing productivity and flexibility. Workers can reposition the light effortlessly, optimizing illumination exactly where it's needed most.



PORTABLE EXPLOSION PROOF LIGHT

Classifications

NEC/CEC Standard

- UL 844 Hazardous Locations
 - Class I Division 1, Group B, C, D
 - Class I Division 2, Group A, B, C, D
 - Class II Division 1, Group E, F, G
 - Class II Division 2, Group F, G
 - Class III
- UL 1598 Wet Locations
- UL 1598A Marine Outside Type (Salt Water)
- UL 8750 LED Safety
- CSA C22.2 No.137-M1981
- CSA C22.2 NO. 250.0

Technical Data

Electric & Optical

Rated Power	Input Voltage
60W	AC100-277, 347-480V
Lumen Output	9600

Luminous Efficacy	160 Lm/W
Beam Angle	110°
Color Temperature	5000K
CRI	Ra>70

Environmental & Technical

Ambient Temperature	-40°C~+65°C
Ambient Humidity	10%~90% RH
Lens Material	Glass
Mounting Options	Quadpod, Magnet Mount / Ladder Bracket / Cart
Cable Entries	3/4" NPT
Net Weight	14.3 LBS

Options And Accessories

- Surge Protection
- L70 > 150,000 operation hours@ 60°C
- 3-year limited light warranty

 sales@worksitelighting.com

 8778615255

 worksitelighting.com

