

# M-FIRE 03 HL

PHH0215


**APPLICATIONS:** FIREFIGHTING, RESCUE, WORK SAFETY, INDUSTRIAL, OIL & GAS, CHEMICALS

POWER SUPPLY	4 x AA			
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE	PEAK BEAM INTENSITY
HIGH	400 lm	8 h 10 min	150 m	5660 cd
LOW	145 lm	13 h 10 min	90 m	1975 cd
DIMENSIONS	172 x 47 x 47 mm			
WEIGHT	140 g (without batteries), 270 g (with batteries)			
THE SET INCLUDES	4 x AA batteries, clip			

## ADDITIONAL ACCESORIES:

RHH0051	Rosenbauer Heroes Titan mount
PHH0012M-UP	Gallet helmet mount
RHH0041	Calisia helmet mount

 **IPX7 RATING**
 **1 m IMPACT RESISTANCE**
 **CLIP**

 **ATEX** No.: II 1G Ex ia IIC T4 Ga, I M1 Ex ia I Ma

M-Fire 03 HL flashlight, with ATEX certification, is designed for safe use in explosion-hazard areas. It combines safety with performance and is suitable for zones with highly explosive gases like hydrogen and acetylene (IIC classification). With 400 lumens and a beam distance of 150 meters, the M-Fire 03 HL delivers powerful illumination, even in harsh conditions. Its IPX7 protection ensures water resistance up to 1 meter for 30 minutes. Powered by four AA batteries, it offers a reliable and easily replaceable power source without needing specialized chargers. The flashlight includes a clip for attachment to clothing or gear and can be mounted on firefighter helmets or paired with a traffic control cone for added versatility.

ANSI FL1 STANDARD

 400 lm

 150 m



**NEW**



PRODUCT MEETS THE FOLLOWING STANDARDS:   

**MACTRONIC®  
VALUE  
HIGHLIGHTS**

**5-YEAR  
WARRANTY**

  
**PATENTED  
DESIGN**

  
**ECO FRIENDLY  
PACKAGING**

**SCAN ME**

